

# WEST Search History





DATE: Thursday, November 10, 2005

Hide?	<u>Set</u> <u>Name</u>	<u>Query</u>	<u>Hit</u> <u>Count</u>
	<i>DB=USPT; PLUR=YES; OP=OR</i>		
<input type="checkbox"/>	L45	6078733 and @ad<19971014	1
<input type="checkbox"/>	L44	6078733	11
<input type="checkbox"/>	L43	(5566170 5878225 5930830 5991299 6034963 6061368).pn.	6
<input type="checkbox"/>	L42	alacritech.as.	18
	<i>DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR</i>		
<input type="checkbox"/>	L41	L38 and @ad<1997	0
<input type="checkbox"/>	L40	L39 and @ad<1997	0
<input type="checkbox"/>	L39	L38 and @ad<19971014	0
<input type="checkbox"/>	L38	alacritech.as.	80
<input type="checkbox"/>	L37	(intelligent adj network adj interface) and @ad<19971014	51
<input type="checkbox"/>	L36	L35 and @ad<19971014	150
<input type="checkbox"/>	L35	(intelligent adj network adj interface) inic	5312
<input type="checkbox"/>	L34	(6009478 6034963).pn.	4
<input type="checkbox"/>	L33	(5996024 6226680 6247060).pn.	6
<input type="checkbox"/>	L32	L31 and @ad<19971014	6
<input type="checkbox"/>	L31	(offload\$3 off-load\$3) with (nic (network adj interface\$3)) with (host\$3 cpu)	125
<input type="checkbox"/>	L30	L29 and @ad<19971014	0
<input type="checkbox"/>	L29	(tcp ip) with (offload\$3 off-load\$3) with (nic (network adj interface\$3))	138
<input type="checkbox"/>	L28	6427171	41
<input type="checkbox"/>	L27	L26 and offload\$3	49
<input type="checkbox"/>	L26	L25 and @ad<19971014	1342
<input type="checkbox"/>	L25	(host cpu) with (nic (network adj interface\$3))	9119
<input type="checkbox"/>	L24	L23 and @ad<19971014	1
<input type="checkbox"/>	L23	6247060	64
<input type="checkbox"/>	L22	6247060	64
<input type="checkbox"/>	L21	L20 and 709/\$.ccls.	12
<input type="checkbox"/>	L20	L19 and ((bypass\$5 offload\$5) with (cpu microprocessor\$3 processor\$5))	72
<input type="checkbox"/>	L19	L18 and @ad<19971014	2189
<input type="checkbox"/>	L18	(microporcessor\$5 processor\$3 cpu) with (nic (network adj interface\$3))	14832
<input type="checkbox"/>	L17	20010025315	2
<input type="checkbox"/>	L16	20010025315	2

<input type="checkbox"/>	L15	5937436	10
<input type="checkbox"/>	L14	L13 and @ad<19971014	2
<input type="checkbox"/>	L13	offload\$5 with (microporcessor\$5 processor\$3 cpu) with (nic (network adj interface\$3))	90
<input type="checkbox"/>	L12	L11	13
<i>DB=USPT; PLUR=YES; OP=OR</i>			
<input type="checkbox"/>	L11	offload\$5 with (microporcessor\$5 processor\$3 cpu) with (nic (network adj interface\$3))	13
<input type="checkbox"/>	L10	L8 and @ad<19971014	15
<input type="checkbox"/>	L9	L7 and @ad<19971014	949
<input type="checkbox"/>	L8	L7 and (offload\$5 with (cpu processor\$3 microporcessor\$5))	56
<input type="checkbox"/>	L7	network adj interface adj card\$3	4484
<input type="checkbox"/>	L6	L5 and @ad<19971014	2
<input type="checkbox"/>	L5	intelligent adj network adj interface adj card\$3	28
<input type="checkbox"/>	L4	6061742.pn.	1
<input type="checkbox"/>	L3	6427171	9
<input type="checkbox"/>	L2	6427171	9
<input type="checkbox"/>	L1	6697868	3

END OF SEARCH HISTORY



[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) <sup>New!</sup> [more »](#)

"offload cpu " "network interface card"

[Search](#)

[Advanced Search](#)  
[Preferences](#)

## Web

Results 1 - 10 of about 22 for "[offload cpu](#) " "[network interface card](#)". (0.35 seconds)

### [Gigabit Ethernet: December 1997 Update](#)

... for your servers that support these features and **offload CPU** in the process. ... a PCI and SBus **network interface card(s)**; a router interface card(s) or ...  
[www.corecom.com/html/gigabit.html](http://www.corecom.com/html/gigabit.html) - 21k - [Cached](#) - [Similar pages](#)

### [Instant Rules of Thumb for Tuning and Sizing NT Server](#)

**Network Interface Card** Settings. Setting the NIC properly is an area that is commonly ... Whenever possible, **offload CPU** operations to secondary devices. ...  
[www.microsoft.com/technet/archive/winntas/maintain/instant.mspix](http://www.microsoft.com/technet/archive/winntas/maintain/instant.mspix) - 254k - [Cached](#) - [Similar pages](#)

### Sponsored Links

#### [Intel Network Card](#)

Extend Gigabit Ethernet performance to PC with Intel® PRO network cards  
[www.intel.com](http://www.intel.com)

#### [Network Interface Card](#)

Bargain Prices.  
You want it, we got it!  
[BizRate.com](http://BizRate.com)

#### [Network Interface Card](#)

**Network interface card** online  
[Shop Target.com](http://Shop.Target.com)  
[www.Target.com](http://www.Target.com)

#### [Network Interface Card?](#)

Brief and Straightforward Guide to **Network Cards**  
[wisegeek.com](http://wisegeek.com)

### [Instant Rules of Thumb for Tuning and Sizing NT Server](#)

... **Network Interface Card** Settings. Setting the NIC properly is an area that is commonly taken for granted. ... **Offload CPU** Intensive Operations. ...  
[www.microsoft.com/technet/prodtechnol/winntas/maintain/instant.mspix](http://www.microsoft.com/technet/prodtechnol/winntas/maintain/instant.mspix) - 101k - Supplemental Result - [Cached](#) - [Similar pages](#)

### [\[PDF\] Windows NT/2000 Performance and Capacity Key Metrics INFORMATION ...](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)  
get info concerning the **network interface card**. Select Start/Settings/Control ... **Offload CPU** intensive work. \* Remove faulty Hardware. ...  
[regions.cmg.org/regions/nycmg/presentations/CMGNTNY01.pdf](http://regions.cmg.org/regions/nycmg/presentations/CMGNTNY01.pdf) - [Similar pages](#)

### [EP1359724](#)

... this capability and developed methods to **offload CPU** intensive tasks and ... TCP connection from the core stack to a **network interface card** (NIC). ...  
[swpat.ffii.org/pikta/bxt/ep/1359/724/](http://swpat.ffii.org/pikta/bxt/ep/1359/724/) - 100k - [Cached](#) - [Similar pages](#)

### [\[PDF\] University of Manitoba](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)  
may be embedded in a **network interface card**, NIC, or host bus adapter, HBA. ... TOE not only **offload CPU** processing to increase application perfor- ...  
[www.phatpackets.com/papers/PhatpacketsTransportOffloadSiliconPotential-WithAppendices.pdf](http://www.phatpackets.com/papers/PhatpacketsTransportOffloadSiliconPotential-WithAppendices.pdf) - [Similar pages](#)

### [\[PDF\] SNA IDIG](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)  
Copyright © 1998-2001 Cisco Systems, Inc. All rights reserved. Important Notices and Privacy Statement. Printed in USA. Catalyst, Cisco, Cisco IOS, ...  
[www.psionic.com/application/pdf/en/us/guest/tech/tk658/c1501/ccmigration\\_09186a008007cd59.pdf](http://www.psionic.com/application/pdf/en/us/guest/tech/tk658/c1501/ccmigration_09186a008007cd59.pdf) - Supplemental Result - [Similar pages](#)

### [Method to offload a network stack patent](#)

... that peripheral device manufacturers tried to do was to offload the entire TCP connection from the core stack to a **network interface card** (NIC). ...  
[www.freshpatents.com/Method-to-offload-a-network-stack-dt20050428ptan20050091412.php](http://www.freshpatents.com/Method-to-offload-a-network-stack-dt20050428ptan20050091412.php) - 21k - Supplemental Result - [Cached](#) - [Similar pages](#)

### [\[PDF\] Monitoring NT Performance](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)  
will get info concerning the **network interface card**. Select start/settings/control ... **offload**

<http://www.google.com/search?hl=en&q=%22offload+cpu+%22+%22network+interfac...> 11/10/05

CPU intensive work. Remove faulty hardware. NT service packs ...  
[www.ohvcmg.org/pdf/CMG02g2.pdf](http://www.ohvcmg.org/pdf/CMG02g2.pdf) - [Similar pages](#)

[\[PDF\] Monitoring NT Performance](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

will get info concerning the **network interface card**. Select Start/settings/control panel/networks/services/add and add the SNMP service. you will ...

[www.srmassoc.com/CMG02g2.pdf](http://www.srmassoc.com/CMG02g2.pdf) - Supplemental Result - [Similar pages](#)

Google

Result Page: 1 2 3 [Next](#)

Free! Get the Google Toolbar. [Download Now](#) - [About Toolbar](#)



"offload cpu " "network interface card" [Search](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google

[Subscribe](#) (Full Service) [Register](#) (Limited Service, Free) [Login](#)Search: ☒ The ACM Digital Library ☐ The Guide

THE ACM DIGITAL LIBRARY

[Feedback](#) [Report a problem](#) [Satisfaction survey](#)

Published before October 1997

Terms used **NIC offload**

Found 1 of 88,246

Sort results by Display results  [Save results to a Binder](#) [Search Tips](#)☐ Open results in a new window[Try an Advanced Search](#)[Try this search in The ACM Guide](#)

Results 1 - 1 of 1

Relevance scale ☐ ☐ ☐ ☐ ☐

# 1 [Computer Communication Networks: Approaches, Objectives, and Performance](#)



## [Considerations](#)

Stephen R. Kimbleton, G. Michael Schneider

September 1975 **ACM Computing Surveys (CSUR)**, Volume 7 Issue 3**Publisher:** ACM PressFull text available: [pdf\(3.99 MB\)](#)Additional Information: [full citation](#), [references](#), [citations](#), [index terms](#)

Results 1 - 1 of 1

The ACM Portal is published by the Association for Computing Machinery. Copyright ?2005 ACM, Inc.

[Terms of Usage](#) [Privacy Policy](#) [Code of Ethics](#) [Contact Us](#)Useful downloads: [Adobe Acrobat](#) [QuickTime](#) [Windows Media Player](#) [Real Player](#)

This is Google's cache of [http://www.snwonline.com/implement/iscsi\\_feasible\\_04-15-2002.asp?article\\_id=114](http://www.snwonline.com/implement/iscsi_feasible_04-15-2002.asp?article_id=114) as retrieved on Nov 4, 2005 19:31:59 GMT.

Google's cache is the snapshot that we took of the page as we crawled the web.

The page may have changed since that time. Click here for the [current page](#) without highlighting.

This cached page may reference images which are no longer available. Click here for the [cached text](#) only.

To link to or bookmark this page, use the following url: [http://www.google.com/search?](http://www.google.com/search?q=cache:bWJLed5E1psJ:www.snwonline.com/implement/iscsi_feasible_04-15-2002.asp%3Farticle_id%3D114+%22network+interface+card%22+%22NIC%22+cpu+host+offload&hl=en)

[q=cache:bWJLed5E1psJ:www.snwonline.com/implement/iscsi\\_feasible\\_04-15-2002.asp%3Farticle\\_id%3D114+%22network+interface+card%22+%22NIC%22+cpu+host+offload&hl=en](http://www.google.com/search?q=cache:bWJLed5E1psJ:www.snwonline.com/implement/iscsi_feasible_04-15-2002.asp%3Farticle_id%3D114+%22network+interface+card%22+%22NIC%22+cpu+host+offload&hl=en)

*Google is neither affiliated with the authors of this page nor responsible for its content.*

These search terms have been highlighted: **network interface card nic cpu host offload**



COMPUTERWORLD

STORAGE NETWORKING WORLD ONLINE



THE ONLINE STORAGE NETWORKING MAGAZINE FOR IT LEADERS

[Subscribe](#) | [About Us](#) | [Resources](#)

search

#### NAVIGATE THE SITE

User Advocates

by Jon William Torgo

Voice of Experience

by Barb Goldworm

Straight Shooting

by Steve Duplessie

Storage Insider

by John Webster

What is Behind the Move to  
Storage Networks

Why Implement Storage Networks

How to Plan/Implement Storage  
Networks

How to Evaluate Success and  
Plan for the Next Step

Case Studies

Tech Edge

Best of Computerworld  
Storage Knowledge Center

Quick Poll

Resource Center

Search Feature

Quote of the Week

## WHY IMPLEMENT STORAGE NETWORKS

ARTICLE POSTED April 15th, 2002

### Thanks to acceleration technologies, iSCSI is feasible

By Larry Boucher

iSCSI is a protocol that has attracted a great deal of attention in the storage industry. With iSCSI, users will be able to create SANs practically anywhere over standard Ethernet cabling — without requiring dedicated Fibre Channel networks to carry the data between the server and the storage devices. With iSCSI, remote mirroring and backup will become readily available because the distance limitations of Fibre Channel will be irrelevant in a world where data is transferred using standard TCP/IP and Ethernet for transport (see companion story on home page, "iSCSI developments bode well for commercial acceptance").

The emergence of Gigabit Ethernet, and the impending move toward 10 Gigabit Ethernet, will enable the transfer of data using iSCSI protocol at full device speeds. However, to perform these high-speed transfers, a new class of network device will be required.

Until recently, the **CPU** in a server or workstation was responsible for managing the TCP/IP processing necessary for sending and receiving data over a network, with a **network interface card (NIC)** providing the actual interface to the network. In the days when CPUs operated at considerably higher speeds than the network data flow, this was not a problem. However, with Gigabit Ethernet, processing of TCP/IP on the **host CPU** has often required as much as 100% of the processor's cycles.

With the addition of iSCSI processing on the **host CPU**, the result will be 100% CPU utilization — in effect, locking the computer for any other processes and significantly reducing network performance, because even

#### USER FEEDBACK

Click here to tell us what  
you thought of the story



**EMAIL THIS ARTICLE  
TO A FRIEND**

Please provide the  
following information.

Your name:

Your E-mail:

Recipient's E-mail:

Message:

**Send**

the fastest **CPU** will be unable to process TCP/IP and iSCSI at full wire speed.

**Offloading server processing**

The solution to this problem involves the use of a "TCP/IP offload engine" (TOE) that offloads some or all of the TCP/IP processing from the server. In essence, a TOE applies the task of TCP/IP processing to one or more chips that are optimized for this task.

With the addition of iSCSI, further processing is required. As with TCP/IP, the iSCSI processing can be done in software on the server **CPU**, or it can be offloaded to a device specially designed to perform the necessary processing. In all cases, however, to achieve the necessary performance for high-speed networking and/or storage processing, the most effective approach is to **offload** the processing from the **host CPU** to a specialized device.

**Three iSCSI implementation approaches**

Three basic approaches are being taken to implement iSCSI connectivity.

**Standard NICs**

Early implementations of iSCSI were proposed using standard Gigabit NICs that left the processing of iSCSI protocol to the **host CPU**. This approach may be the fastest to market because it simply incorporates standard components. But this simple approach is not viable because it requires considerable **CPU** resources. In most cases, the **host CPU** will run at 100% simply to process TCP/IP and iSCSI, and no resources will be available for other computing processes.

Even assuming 100% utilization of a Gigahertz processor, protocol processing with this approach will likely not keep up with wire-speed data transfer, especially when more than one network port or NIC is coupled to the **CPU**. Thus, although this approach supports Ethernet failover, load balancing and link aggregation, its poor performance makes it unacceptable for nearly all users.

**Full-offload iSCSI HBAs**

Taking a cue from the Fibre Channel world, a number of vendors are building iSCSI **host** bus adapters (HBAs). This new class of product uses a **full-offload** approach for iSCSI and TCP/IP protocol processing.

**Full-offload** adapters remove the entire TCP/IP stack from the **host CPU**. As a result, the **host** and network do not see the iSCSI adapters as NIC controllers. These cards are not designed to handle generalized networking tasks. For instance, the method for performing failover and link aggregation will not be able to follow a standard Ethernet implementation. **Full-offload** cards may use traditional storage failover facilities such as Active-Active designed for Fibre Channel.

For an iSCSI HBA, TCP/IP and iSCSI protocol processing may be performed on an embedded processor with either a standard Gigabit Ethernet controller or a specially designed application-specific integrated circuit (ASIC). Intel's recently announced PRO/1000 T IP Storage Adapter uses an Intel 80200 (XScale) processor with a standard GbE controller to perform the TCP/IP and iSCSI processing tasks.

Intel claims to have been able to transfer data over iSCSI at speeds ranging from 37.5M bps to 87.5M bps, with 3% to 5% **CPU** usage. However, without data on how the test was run, it is difficult to accurately compare this card's performance with that of other products.

Adaptec is attempting an ASIC implementation, supplementing the Intel 80200 processor with its Storage Protocol Accelerator (SPA) — AIC-7211 ASIC in the ASA-7211 iSCSI Adapter. Like the Intel card, the Adaptec iSCSI HBA uses an Xscale processor. At this time, however, the company has not provided any specifics relating to data throughput or the amount of **CPU** cycles required during data transmissions.

# Find

#### **Data-path offload IS-NIC**

The term "integrated storage **network interface card**" (IS-NIC) refers to an adapter that can be used as a network interface for moving Ethernet file data, as a storage interface for moving iSCSI block data, and as a dual-purpose card functioning as a NIC and as an iSCSI device simultaneously. This approach offers the advantages of both the iSCSI HBA and the standard NIC, while offering none of the disadvantages associated with isolating these functions.

Rather than move the entire protocol stack onto the adapter, an IS-NIC uses a technique called **data-path offload**; namely, data movement is performed in a custom-designed ASIC, and the TCP connection and error management is handled in **host** software. Although the **host CPU** may rarely have to control the data path, it is advantageous for the **host CPU** to be able to take control of the data path under certain conditions, such as error management.

Being able to control data flow enables the **host** computer to perform failover, load balancing and link aggregation using Ethernet standard protocols. If the **host CPU** or the network switch detects that one iSCSI card or link is handling a disproportionate amount of data, it can redistribute the data to other iSCSI cards.

The **data-path offload** approach eliminates the need to design a large, complex chip for rare error occurrences and enables the smallest footprint and the most power-efficient design for TCP/IP and iSCSI **offload**.

The Alacritech 1000x1 Single-Port Server and Storage Accelerator, which began shipping in October 2001, implements **data-path offload** for TCP/IP and iSCSI traffic. The **data-path offload** solution provides comparable or better performance and efficiency, compared with any Fibre Channel or iSCSI HBA. Alacritech recently reported successful wire-speed transfers of 219.64M bps with less than 8% **CPU** utilization for this Gigabit Ethernet IS-NIC. Testing was performed with a Nishan IP storage switch that converted iSCSI into Fibre Channel and moved the data to a Hitachi Data Systems SAN device.

#### **An evolving standard**

Although iSCSI adapters are currently available, the iSCSI specification has not yet been approved by the Internet Engineering Task Force (IETF). Approval is expected by mid-2002.

Because the specification may undergo additional modifications before an approved spec is agreed upon, it will be impossible to guarantee absolute adherence to the spec prior to its release. However, it is very safe to assume that vendors that are developing iSCSI cards are working hard to assure compatibility, irrespective of the final completion of the spec.

#### **What the future holds**

iSCSI is a logical step forward in the control of data devices. It eliminates the need for specialized HBAs in servers and workstations and allows block-level data to be transferred over a standard Ethernet network.

It will be interesting to see how the industry reacts to the various iSCSI alternatives — the processor-based iSCSI adapter that performs full **offload**, the ASIC-based card that performs full **offload**, and a programmable ASIC device that performs **data-path offload**. What should be clear, however, is that the industry is already responding with iSCSI devices, and that iSCSI is gaining momentum as a significant storage protocol.

In this article, we've looked at the three basic methods for implementing iSCSI as an initiator on the server side. Vendors are working on iSCSI-to-Fibre Channel gateways that provide an iSCSI interface to present Fibre Channel SANs. Although the number of iSCSI products currently available is small, it is clear that many vendors are hard at work developing highly compatible iSCSI products.



Larry Boucher is the Chairman and CEO of Alacritech, Inc.

Feedback: [feedback@snwonline.com](mailto:feedback@snwonline.com)  
Questions: [questions@snwonline.com](mailto:questions@snwonline.com)  
Technical difficulties: [webmaster@snwonline.com](mailto:webmaster@snwonline.com)

**Sponsored Links:**

Storage Knowledge Center      [Computerworld's vast collection of resources on Storage](#)



[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) <sup>New!</sup> [more »](#)

"network interface" "host" "offload"

[Advanced Groups Search](#)

[Preferences](#)

1  Jan  1981  - 14  Oct  1997

Members: [Sign in](#)

New users: [Join](#)

Recently visited [\[clear\]](#)

[comp.os.ms-w...g.tcp-ip](#)

[comp.protocols.tcp-ip](#)

[comp.unix.questions](#)

☒ [Groups Alerts](#)

[Create a new group](#)

[About Google Groups](#)

## Searched all groups

Results 1 - 9 of 9 from Jan 1, 1981 to Oct 14, 1997 for "network interface" "host" "offload" (0.09 seconds)

[Sorted by relevance](#) [Sort by date](#)

### "host-based" vs. "front-end-processor" PC network interfaces

... and acknowledgement o partially **offload** keystroke processing ... Separation between the **host** and onboard portions is ... The EXOS205 **Network Interface Card** for PC's is ...

[comp.protocols.tcp-ip.ibmipc](#) - May 12 1988, 8:34 pm by Chuck Kollars - 3 messages - 3 authors

### multiple IP addrs on single net interface

... This **host** has a single **network interface**. ... HP gotcha #2: The code will almost certainly not work on interfaces using checksum **offload** (eg. FDDI). ...

[comp.unix.questions](#) - Mar 11 1995, 5:14 am by Steinar Haug - 4 messages - 4 authors

### Shared memory comm. on HP machines, possible?

... go to that hosts primary "real" **network interface** (such as lan0 ... not think that there is checksum **offload**, and will ... If instead, you add some **host** routes for your ...

[comp.parallel.pvm](#) - Jun 23 1994, 7:52 pm by Rick Jones - 6 messages - 6 authors

### DISPLAY=:0.0

... X calls go thru **network interface** if "host:0" is ... will go part-way into the **network interface's \_driver\_** but ... to have a larger MTU and provides checksum **offload**. ...

[comp.sys.hp.hpux](#) - Nov 8 1996, 5:15 pm by Rick Jones - 19 messages - 14 authors

### Fragen zu Protokollen

... Processing Environment" protocol, may be employed to **offload** Network and ... be erected

on an ARM LI - L II (**Network Interface** and **Host-Host Layers**) "foundation ...

[de.comp.standards](#) - Nov 15 1994, 6:41 pm by Kai Henningsen - 9 messages - 7 authors

### Linux/tcpdump/NIC cards (traffic analysis)

... want a "smarter" nic card that will **offload** some of the ... gives a breakdown of traffic

by **host** Let me ... does it use to put the **network interface** into promiscuous ...

[comp.protocols.tcp-ip](#) - Oct 5 1997, 7:24 am by Aaron Newsome - 7 messages - 7 authors

### new Inmos Transputer ( was Re: 88000 Question )

So you **offload** the protocol processing to a dedicated ... 100Mbps to the general purpose

**host** running Unix? ... because a transputer doesn't have a **network interface**. ...

[comp.sys.next.misc](#) - Jul 29 1991, 2:56 am by Scott Hess - 57 messages - 29 authors

### Introduction to TCP/IP Administration by Chuck Hendrick

... the machine has more than one **network interface**, you must ... point lines or switched

lines directly to each **host**. ... It often makes sense to **offload** the routing and ...  
[comp.os.ms-windows.networking.tcp-ip](#) - Dec 1 1995, 5:37 am by Greg E Hersh -  
1 message - 1 author

[Embedded Processor and Microcontroller primer and FAQ](#)

... a dedicated [co]processor to **offload** some of ... for another keystroke, or  
information  
from the **host**. ... multi-master, multi-slave **network interface** with collision ...  
[comp.robotics.misc](#) - Oct 1 1996, 7:23 pm by Russ Hersch - 1 message - 1 author

*In order to show you the most relevant results, we have omitted some entries very  
similar to the 9 already displayed.*

*If you like, you can [repeat the search with the omitted results included](#).*

 

[Google Home](#) - [Terms of Use](#) - [Privacy Policy](#) - [Jobs, Press, & Help](#)

©2005 Google